UNPAINTED UNASSEMBLED FIGURE / 未塗装未組立キット(フィギュア)

Instruction Manuals [English/英語版]

Product Features

This product is an unassembled variant of the "Pre-painted, Pre-assembled PVC Statue ASRA NINJA" that was released in January 2023.

Unlike other Kotobukiya statue and model kit products, the design is intended to be assembled by factories and not end users. Because of that, some parts require manual adjustment of their fit and shape using tools by end users. Assembly requires some knowledge and skills in the use of the materials, adhesives, and necessary tools. Please enjoy with these features in mind.

■ The materials used are mostly PVC and ABS. Please use instant adhesives for gluing the parts together.

- If the parts are both made of ABS, specialized ABS adhesives can be used as well.
- Almost all parts will have unfinished sprue marks and plastic burrs from the molding process. Please be aware of the following.
- Due to their shapes, it may be unclear whic parts require removal. Please make sure to attempt temporary assembly to confirm if adjustment is necessary before sanding, cutting, or gluing.
- Please use a sturdy set of nippers (cutter knives and carving knives can be used as well) for removal of unnecessary materials. Use of thin and precise blades like those on precision nippers may damage the blade.
- Please be careful not to injure yourself when making adjustments using these bladed tools.

Certain types of thinners in the paint may attack and degrade the ABS plastic, leading to more brittleness and overall weakening of the parts.

- For painting the ABS parts, please use surfacer or primers for model kits to form a protective coating before applying paint.
- Even after forming the protective coating, please do not use paints with a lot of thinner to avoid chemical degradation.



[Kotobukiya Official Website: How to Paint ABS Parts] URL : https://www.kotobukiya.co.jp/en/page-21029/


- PVC is a soft material, and can deform if enough force is applied. Such deformations can be corrected by heating the parts using hair dryers or hot water, and then bending it back to shape.
- When doing so, please use warm water at a temperature that you can touch. Be aware of burns.


- After about 10 seconds the parts will become soft, depending on the temperature. Be sure to check the progress, especially thin portion of the parts as they become soft faster.
- ■When painting ABS parts, please be aware of the following.
- Usually paint thinners should not affect the overall integrity of the parts but may cause degradation on the surface. Do not expose the parts to paint thinners for a long time.
- Paint layers on statues tend to be less durable than those on plastic model kits. We recommend using primer to treat the surface for a more durable paint layer.
- Bending, pushing, or otherwise deforming the parts may cause the layer to peel off. Please be careful during assembly. Also, standard model-kit paint tends to have very limited elasticity after drying and will not conform to any adjustments.




URL : https://www.kotobukiya.co.jp/blog2/megami/article/detail/252/


Unfortunately the guide article is in Japanese only. We apologize for your inconvenience.






































L – Assemble Left Arm










O - Assemble Left Right Armor













P - Assemble Right Leg
























U – Assemble Left Hand Weapon









Combine Left Arm







Left Hand Weapon



Attach Right Thigh Weapon






Complete Assembly






Attach Decals

Decals



Attaching Decals		rs or a hobby knife, tweezers, and cotton swabs. ks on easily if the oil on the sticky part is removed with detergent first.
 Do not touch the decal until it has dried complete when the decal is completely dry. Decals cannot be attached to rough surfaces or surfaces that absorb (i.e. rough, unpainted wooden products). To remove a mistakenly attached decal, place a thoroughly wet tow minutes and lightly rub the decal off. 	en remove with osition. ning water. It is o water	 (Tips for Attaching Decals to Curved Surfaces) Decals attach smoothly to curved surfaces when softened first with decal softener (sold separately). Additionally, through the use of surface finishing spray (sold separately), the decal will be more resistant to ripping or tearing. *When removing and attaching parts to your model, make sure to not touch the surface you have attached the decal to. *Decals rip easily after the use of decal softener. Make sure to not touch the decal until it has fully dried. If a white space appears, you can either cut it out along the shape of the part, or fold it to the inside. *When using decal softener and surface finishing spray, make sure to follow the product's directions.

Decal Guides Megami Device ASRA NINJA Modeler's Edition *Attach the decals in brackets on the opposite side.






Decal Guides Megami Device ASRA NINJA Modeler's Edition ** Attach the decals in brackets on the opposite side.

-36 (36)

(39)








Left Hand Weapon

38 (38)







Right Hand Weapon